

DESCRIPTION AND USE

Stand Off® Color Enhancer brings out the color, warmth and richness of interior limestone, marble, granite and other unpolished natural stone surfaces. Treated surfaces not only look better but resist destructive water penetration and staining from a wide range of contaminants, including oil, grease, food and drink, and dirt.

Color Enhancer is perfect for stone counters and tabletops, and stone and terrazzo floors. This penetrating protective treatment won't trap moisture or create a surface sheen. Treated surfaces keep their natural texture.

ADVANTAGES

- Safe alternative to linseed oil-based materials.
- Low odor.
- Penetrates deeply without producing a shiny surface film.
- Surfaces can be re-treated.
- Reduces staining, oil and water penetration.
- Complies with all known national and state AIM VOC regulations.

Limitations

- Will not bond to cementitious adhesives. Test for bondability to new products.
- Not for use on exterior surfaces.
- Not for use on polished or most dense surfaces.
- Not for use around pools or fountains.
- Will not compensate for structural or surface defects.
- Not available in South Coast Air Quality Management District except in regulation-exempt container sizes.

TYPICAL TECHNICAL DATA

FORM: Amber liquid, low odor
SPECIFIC GRAVITY: 0.868
TOTAL SOLIDS*: 54%
pH: NA
WT/GAL 7.22 lbs.
FLASH POINT: >100°F (38°C)
FREEZE POINT: NA
SHELF LIFE: 1 year in tightly sealed, unopened container

VOC Information

US EPA: maximum VOC content 600 g/L
CARB: maximum VOC content 400 g/L
NEOTC: maximum VOC content 400 g/L
Maricopa County, AZ: maximum VOC content 400 g/L

PREPARATION

Surface should be clean and dry. Remove all dust, dirt, oil, grease and other contaminants using the appropriate Sure Klean®, Stand Off® or Enviro Klean® cleaner. Let newly installed grout cure for 72 hours before application.

Ensure fresh air entry and cross ventilation during application and drying. Extinguish all flames, pilot lights and other potential sources of ignition during use and until all vapors are gone. Avoid exposing passersby and building occupants to product, fumes and mists.

Surface and Air Temperatures

40-90°F (4-32°C) and for 4 hours after application. On warm days, apply early in the day and to shaded areas.

Equipment

Apply with a brush, low pressure sprayer or lint-free cloth.

Storage and Handling

Store in a cool, dry place away from potential ignition sources. Keep tightly closed when not dispensing. Published shelf life assumes upright storage of factory-sealed containers in a dry place. Maintain temperatures of 45-100°F (7-38°C). Do not double stack pallets. Dispose of unused product and container in accordance with local, state and federal regulations.

APPLICATION

Before use read "Preparation" and "Safety Information."

ALWAYS TEST each surface for suitability and desired results before overall application. Use the following application instructions. Let dry thoroughly before inspection and approval.

Dilution

Do not alter or dilute.

Coverage Rates

Coverage varies based on porosity and texture. Always test. Not recommended for non-porous surfaces. Coverage is in sq.ft./m. per gallon of concentrate.

Porous	75-100 sq.ft. / 7-9 sq.m.
Semi-porous	100-150 sq.ft. / 9-14 sq.m.

Application Instructions

1. Protect baseboards and nearby surfaces from contact. Apply a heavy, even coat. Saturate the surface
 2. Let product penetrate the surface for 5 minutes.
 3. Wipe excess off with a clean, dry cloth. Excess product may leave residues which are difficult to remove.
 4. Let treated surfaces dry overnight.
 5. If needed for porous, absorbent surfaces or for more color enhancement, apply a second coat after first coat is fully dry.
- Protect treated surfaces from foot traffic for 24 hours.

Cleanup

Clean equipment with mineral spirits, paint thinner or similar solvents. Cloth and paper soaked in product may spontaneously ignite. Place in water or spread to dry immediately after use. Container may retain residues. Keep from ignition sources. Do not reuse.

SAFETY INFORMATION

Stand Off[®] Color Enhancer is a solvent carried product and may cause symptoms typical with organic solvent exposure. This is a combustible material. Use appropriate ventilation, safety equipment and job site controls during application and handling. Read the full label and MSDS for precautionary instructions before use.

First Aid

Ingestion: Call physician immediately.

Eye Contact: Rinse eyes thoroughly for 15 minutes. Get medical attention.

Skin Contact: Rinse thoroughly. Get medical attention if irritation persists.

Inhalation: Remove to fresh air. Give artificial respiration if not breathing. Get immediate medical attention.

24-Hour Emergency Information: INFOTRAC at 800-535-5053

WARRANTY

The information and recommendations made are based on our own research and the research of others, and are believed to be accurate. However, no guarantee of their accuracy is made because we cannot cover every possible application of our products, nor

anticipate every variation encountered in masonry surfaces, job conditions and methods used. The purchasers shall make their own tests to determine the suitability of such products for a particular purpose.

PROSOCO, Inc. warrants this product to be free from defects. **Where permitted by law, PROSOCO makes no other warranties with respect to this product, express or implied, including without limitation the implied warranties of merchantability or fitness for particular purpose.** The purchaser shall be responsible to make his own tests to determine the suitability of this product for his particular purpose. PROSOCO's liability shall be limited in all events to supplying sufficient product to re-treat the specific areas to which defective product has been applied. Acceptance and use of this product absolves PROSOCO from any other liability, from whatever source, including liability for incidental, consequential or resultant damages whether due to breach of warranty, negligence or strict liability. This warranty may not be modified or extended by representatives of PROSOCO, its distributors or dealers.

CUSTOMER CARE

Factory personnel are available for product, environmental and job-safety assistance with no obligation. Call 800-255-4255 and ask for Customer Care - technical support.

Factory-trained representatives are established in principal cities throughout the continental United States. Call Customer Care at 800-255-4255, or visit our web site at www.prosoco.com, for the name of the Stand Off[®] representative in your area.

*PROSOCO Technical Data for film-forming protective treatments reports Total Solids as measured by ASTM D 2369 - Standard Test Method for Volatile Content of Coatings. The active content is calculated based on raw materials used in the formulation. Active Content for this product is 54%.