TOWN HALL™

With more substantial proportions than Copthorne®, Town Hall is cast from original brick street pavers and offers a distressed, time-worn appearance. As well, with Unilock's ever-increasing focus on permeable pavers, Town Hall has been designed to satisfy both traditional and permeable installation methods.

WHY CHOOSE ENDURACOLOR PLUS ARCHITECTURAL FINISHES

EnduraColor Plus Architectural Finishes promise long-lasting beauty through a proprietary blend of exclusive and superior ingredients. A complex blend of granite and quartz, some of nature's highest performing minerals, are combined with color pigments that are highly resistant to fading under UV light and extreme weather conditions. This combination is used to create ultra-realistic surface textures and unique style options that are exceptionally durable. A NEW STANDARD FOR EVERLASTING BEAUTY.

COLORS

BURGUNDY RED

BURNT CLAY

OLD OAK

3 COLOR BLEND
BLENDED ON SITE

BASALT

HERITAGE RED

HERITAGE CLAY

HERITAGE BLEND
BLENDED ON SITE

SHAPES & SIZES

STANDARD
25 CM X 10 CM X 7 CM
9.75" X 4" X 2.75"

STANDARD HALF BUNDLE
25 CM X 10 CM X 7 CM
9.75" X 4" X 2.75"

LEARN ABOUT TOWN HALL TOWN HALL TORTURE TEST

FEATURES

Applications

Borders & Accents

Commercial Vehicular

Pedestrian

Residential Vehicular

Technologies

EnduraColor™ Facemix Technology

EnduraColor products are manufactured in a two-step process which combines a base of coarser aggregates for a stronger foundation, with concentrated color and wear-resistant finer aggregates on top. EnduraColor products are highly resistant to fading because the top layer prevents large, lighter color aggregates from showing through.

Reala™ Surface Technology

Ultra-realistic textures cast from actual natural stone, brick and cobblestones.

Ultima™ Concrete Technology

For heavy traffic loads, this proprietary manufacturing process creates pavers and walls with up to 4 times the strength of poured concrete.

Surface Texture

Timeworn

PATTERNS



Town Hall A
Standard (100%)



Town Hall B
Standard (100%)



Town Hall C
Standard (100%)



Town Hall D
Standard (100%)



Town Hall A Half Bundle
Standard Half Bundle (100%)



Town Hall B Half Bundle
Standard Half Bundle (100%)



Town Hall C Half Bundle
Standard Half Bundle (100%)



Town Hall D Half Bundle
Standard Half Bundle (100%)

PACKAGING

	Unit Thickness	Sq. Ft. Bndl.	Sq. Ft. Layer	Layers Bndl.	Ln Ft Bndl. Soldier	Sq Ft Ln Ft Soldier	Units Sq. Ft.	Lbs Bndl.	Units Bndl.
Rectangle	-	88.41	11.05	8	105	-	-	2912	320.04
Standard Half Bundle	7	44.2	11.05	4	52.49	0.84	3.62	1456.34	160

Town Hall™ Old Oak, Burgundy Red, Burnt Clay Blend - Sold Separately/Blended on Site

Town Hall™ Heritage Red, Heritage Clay, Basalt Blend - Sold Separately/Blended on Site

Additional Town Hall™ Information

Sold in full or half bundles only on a refundable skid. All measurements are nominal. Important: Textured surfaces require a buffer between the plate compactor and the paver surface to prevent scuffing. Take extra care when using Polymeric Sand with this product. Call for more information.

IMPORTANT INFORMATION

Town Hall Street Pavers combine the timeless beauty of historic clay bricks with the functionality, performance and colorfastnessthat only EnduraColor Plus pavers from Unilock can deliver. This paver can be used with both permeable and traditional installation methods.

Base Requirement & Bedding Course – standard or open graded paver base specification.

Handling & Installation – A protective pad is required when doing the final paver compaction. Install from multiple pallets forbest color distribution.

Accent compatibility

- all paver applications and can be used as a wall accent.

Jointing Material and Joint Stabilization

- Good: Ordinary dry joint sand stabilized by a water-based or solvent based joint sand stabilizer sealer

(for impervious installations only)

- Better:

o Non- pervious - Unicare Polymeric Sand, Techniseal RG+, Alliance XP

o Permeable – Select graded stone chips

- Best:

o Non- pervious - Alliance Sand – Eurostone or Polymeric Sand MAX

o Permeable – Unilock EasyPro Joint Compound

o Overlays - Alliance Gator Maxx Polymeric Sand

Note:

o Polymeric sand is often installed too high in the joint. Ensure the sand level is lower than the paver surface to allowfor a three dimensional appearance.

Sealers

- Product may be sealed but it is not absolutely required
- sealers generally decrease the slip resistance of a product
- Unilock Unicare, Surebond, BP Pro and Techniseal sealers can be used.
  - Semi-gloss sealers will still appear glossy on this product. Please test a stone to ensure the desired effect.
- Product must be cleaned before sealing

Cleaners – Any paver cleaner from Unilock, Techniseal, Surebond or BP- Pro is acceptable.

Special note: Other than overlay on concrete stoops and steps, you should have a bedding layer between the pavers and the poured concrete surface to avoid issues with height variance

All measurements are nominal

Colors, product data, and availability are subject to change without notice. Please confirm all details with your local Unilock Dealer or call 1-800-UNILOCK (1-800-864-5625) for availability in your area. The colors shown should only be used as a guide. Final color selections should always be made from actual samples.