



PROSOCO®

# Sure Klean®

CLEANING & PROTECTIVE TREATMENTS

## Residential BrickKLEAN Plus

Sure Klean® Residential BrickKLEAN Plus dissolves hardened mortar and construction dirt on newly constructed residential brick and stone for easy rinsing away. Residential BrickKLEAN Plus removes mortar smears, efflorescence and common construction soiling from brick, tile, concrete and natural stone.

### REGULATORY COMPLIANCE

#### VOC Compliance

Sure Klean® Residential BrickKLEAN Plus is compliant with all national, state and district VOC regulations.

### TYPICAL TECHNICAL DATA

<b>FORM</b>	Clear, amber liquid Pungent odor
<b>SPECIFIC GRAVITY</b>	1.12
<b>pH</b>	0.3 @ 1:6 dilution
<b>WT/GAL</b>	9.40 lbs
<b>FREEZE POINT</b>	<-22° F (<-30° C)
<b>SHELF LIFE</b>	3 years in tightly sealed, unopened container

### SAFETY INFORMATION

Always read full label and SDS for precautionary instructions before use. Use appropriate safety equipment and job site controls during application and handling.

**24-Hour Emergency Information:**  
INFOTRAC at 800-535-5053

### ADVANTAGES

- Safer than muriatic acid.
- Economical concentrate – dilutes with fresh water.
- Cold-water rinse leaves brick clean and uniform without streaking or burning.
- Removes mortar and grout smears and construction dirt.

- Controls green vanadium and brown manganese staining on color-sensitive brick and tile.
- Removes efflorescence on new brick, concrete block, and stone construction.
- Safe for use on most unpolished natural stone or cast stone.
- Designed for use with colored mortar.

### Limitations:

- Not for use on polished surfaces, including marble, limestone or travertine.
- Not designed for manufactured stone substrates. Please consult the stone manufacturer for cleaning recommendations.
- Not intended to remove atmospheric staining. Contact PROSOCO for cleaner recommendations.
- Repeated applications may leave a detergent residue. To reduce potential for detergent residue, always pre-wet; rinse thoroughly; and do not exceed two applications.
- May damage exposed low-E glass treatments; acrylic and polycarbonate sheet glazing; and glazing with surface-applied reflective, metallic or other synthetic coatings and films. Modern soft coat or hard coat low-E glass is not intended to be on the external face of the glass and should not be exposed to or adversely affected by proper cleaning. Always test for adverse effects prior to overall application. If testing is not feasible or indicates adverse effects, such substrates must be protected.

### PREPARATION

Protect people, vehicles, property, metal, painted surfaces, plants and other non-masonry materials from product, splash, residue, wind drift and fumes.

Vapors and liquid can damage a variety of metals and fabrics. Clean masonry before installing windows, doors, metal fixtures, light fixtures, hardware, decorative paving, painted surfaces, plants and other nearby non-masonry items. If already installed, protect with plastic sheeting. If

# Product Data Sheet

## Sure Klean® Residential BrickKLEAN Plus

needed, install temporary barriers to direct cleaning rinse waters away from nearby plants.

Clean mortar and grout staining within 14–28 days of installation. Remove high-strength mortar and grout staining within 7 days.

Water in walls contributes to efflorescence and other staining. Protect open wall cavities from rain during construction.

Remove severe metallic staining using PROSOCO's 800 Stain Remover or Ferrous Stain Remover.

### Surface and Air Temperatures

Surface and air temperatures should be 40°F (4°C) and rising. Do not clean when temperatures are below freezing or will be overnight.

Conduct tests under weather conditions which are similar to those anticipated during clean down. Cleaning results are affected by temperature. Increase dwell time and reduce dilution ratio during cold weather.

### Equipment

Use acid-resistant rigging and safety equipment.

**Small Areas:** Apply diluted cleaner with a soft-fibered masonry washing brush. Scrub with a plastic or brass bristle scrub brush. Do not use brushes with steel bristles. Rinse treated surfaces with a garden hose.

**Large Areas:** Apply diluted cleaner with low-pressure (50 psi max) sprayer fitted with acid-resistant hoses and gaskets and a shower-type spray nozzle for even distribution of the cleaning solution. Do not atomize. Scrub with a plastic or brass-bristle scrub brush. Do not use brushes with steel bristles.

Rinse treated surfaces at 400–1000 psi with a water flow rate of 6–8 gpm for best water/pressure combination. Use a 15–45° fan spray tip. Heated water may improve results. Adjust water pressure and flow rates for sensitive surfaces. Rinsing pressures greater than 1000 psi and fan spray tips smaller than 15° may damage sensitive masonry. Water flow rates less than 6 gpm may slow cleaning and contribute to uneven results.

### Storage and Handling

Store in a cool, dry place with adequate ventilation. Vapors and liquid can damage a variety of metals and fabrics. Provide adequate ventilation. Do not alter or mix with other chemicals. Always seal container after dispensing. Published shelf life assumes upright storage of factory-sealed containers in a dry place. Maintain temperature of

45–100° F (7–38° C). Do not double stack pallets. Dispose of unused product and container in accordance with local, state and federal regulations.

### APPLICATION

Read “Preparation” and the Safety Data Sheet before use.

**ALWAYS TEST** a small area (minimum 4-ft x 4-ft) of each surface to confirm suitability and desired results before beginning overall application. Test each type of masonry and each type of stain. Test with the same equipment, recommended surface preparation and application procedures planned for general application. Let test area dry 3–7 days before inspection and approval. Make the test panel available for comparison throughout the cleaning project.

### Dilution

Dilute by pouring cold water into an empty plastic bucket or sprayer, then add cleaner. No metal buckets or metal sprayers. Add one part cleaner to 4–12 parts cold water, depending upon surface to be cleaned. Do not dilute with hot water. Do not alter or add other chemicals, especially bleach. Always test to find the dilution that cleans best.

### Typical Coverage Rates

Coverage rates vary based on porosity and texture. Always test. Coverage is per gallon of concentrate.

- *Porous, Textured Surfaces:* 300–400 sq.ft. (28–37 sq.m.) per gallon of concentrate
- *Semi-Porous Surfaces:* 500–900 sq.ft. (46–84 sq.m.) per gallon of concentrate
- *Dense, Smooth Surfaces:* 600–1100 sq.ft. (56–102 sq.m.) per gallon of concentrate

### Application Instructions

1. Before applying the prepared cleaning solution, thoroughly prewet the surface with fresh water, working from the bottom to the top.
2. Apply the diluted cleaning solution freely. Clean from the bottom to the top keeping all lower surfaces thoroughly rinsed with water. Inadequate prewetting or rinsing may leave unsightly cleaning residues. Do not hold back on the water.
3. Leave cleaner on the surface 3–5 minutes. Do not let it dry. Rinse lower surfaces with fresh water to prevent streaking.
4. Gently scrape off heavy build-up of excess mortar using a wood scraper or piece of brick. Reapply cleaner and scrub areas of heavy soiling. Be careful not to harm the masonry surface.



# Product Data Sheet

## Sure Klean® Residential BrickLEAN Plus

5. Rinse thoroughly with fresh water until masonry is completely clean. Rinse from the bottom of the work area to the top. Pre-rinse with low pressure water before pressure washer rinsing to reduce damage caused by wind drift. Thorough rinsing is extremely important to ensure that all residues are removed from the porous masonry.
6. Reapply as needed following steps 1–5.

### Cleanup

Clean tools with fresh water. Use fresh water to wash stray cleaner and rinse water off nearby surfaces.

### WARRANTY

The information and recommendations made are based on our own research and the research of others, and are believed to be accurate. However, no guarantee of their accuracy is made because we cannot cover every possible application of our products, nor anticipate every variation encountered in masonry surfaces, job conditions and methods used. The purchasers shall make their own tests to determine the suitability of such products for a particular purpose.

PROSOCO, Inc. warrants this product to be free from defects. **Where permitted by law, PROSOCO makes no other warranties with respect to this product, express or implied, including without limitation the implied warranties of merchantability or fitness for particular purpose.**

The purchaser shall be responsible to make his own tests to determine the suitability of this product for his particular purpose. PROSOCO's liability shall be limited in all events to supplying sufficient product to re-treat the specific areas to which defective product has been applied. Acceptance and use of this product absolves PROSOCO from any other liability, from whatever source, including liability for incidental, consequential or resultant damages whether due to breach of warranty, negligence or strict liability. This warranty may not be modified or extended by representatives of PROSOCO, its distributors or dealers.

### CUSTOMER CARE

Factory personnel are available for product, environment and job-safety assistance with no obligation. Call 800-255-4255 and ask for Customer Care – technical support.

Factory-trained representatives are established in principal cities throughout the continental United States. Call Customer Care at 800-255-4255, or visit our website at [prosoco.com](http://prosoco.com), for the name of the PROSOCO representative in your area.

